

Tube End Facing Machine

NFM - 1625

Features:-

This is a very COMPACT, LIGHT WEIGHT & POWERFUL Machine to Face, Bevel & Weld Preparation for Condenser, heat-Exchanger tubes. Available in Electrical & Pneumatic Version



Drive	Pneumatic	Electric
Locking Range (mm)	20-42	20-42
Ideal Speed (RPM)	400	250
Torque (Nm)	27.5	45.0
Feeding Stroke (mm)	23	23
Pneumatic Power (HP)	0.60	N.A.
Air Consumption (cfm)	16	N.A.
Air Pressure (psi)	90	N.A.
Electric Power (watts)	N.A.	650
Weight (kg)	5.5	5.5

NFM - 3000

Features:-

This is a MOST POPULAR & POWERFUL Machine to Face, Bevel & Weld Preparation for boiler tubes. Available in Electrical & Pneumatic Version



Drive	Pneumatic	Electric
Locking Range (mm)	28-76	28-76
Ideal Speed (RPM)	110	140
Torque (Nm)	84	138
Feeding Stroke (mm)	40	40
Pneumatic Power (HP)	0.83	N.A.
Air Consumption (cfm)	42	N.A.
Air Pressure (psi)	90	N.A.
Electric Power (watts)	N.A.	595
Weight (kg)	9.5	11.0

NFM - 4500

Features:-

This is a HEAVY DUTY, POWERFUL Machine to Face, Bevel & Weld Preparation for heavy wall thickness tubes. Available in Electrical & Pneumatic Version



Drive	Pneumatic	Electric
Locking Range (mm)	39-104	39-104
Ideal Speed (RPM)	60	60
Torque (Nm)	220	240
Feeding Stroke (mm)	40	40
Pneumatic Power (HP)	1.3	N.A.
Air Consumption (cfm)	40	N.A.
Air Pressure (psi)	90	N.A.
Electric Power (watts)	N.A.	1800
Weight (kg)	21.0	23.0

Tube End Facing Machine

NFM - 8000

Features:-

This is a HEAVY DUTY, POWERPUL Machine to Face, Bevel & Weld Preparation for wide range heavy wall thickness tubes. Available in Electrical & Pneumatic Version



Drive	Pneumatic	Electric
Locking Range (mm)	51-203	51-203
Ideal Speed (RPM)	40	40
Torque (Nm)	240.0	240.0
Feeding Stroke (mm)	23	40
Pneumatic Power (HP)	1.3	N.A.
Air Consumption (cfm)	40	N.A.
Air Pressure (psi)	90	N.A.
Electric Power (watts)	N.A.	1800
Weight (kg)	26.5	30.0

NFM - 12000

Features:-

This is a HEAVY DUTY, POWERPUL Machine to Face, Bevel & Weld Preparation for wide range heavy wall thickness tubes. Available in Electrical & Pneumatic Version



Drive	Pneumatic	Electric
Locking Range (mm)	88-306	88-306
Ideal Speed (RPM)	35	31
Torque (Nm)	180	230
Feeding Stroke (mm)	50	50
Pneumatic Power (HP)	1.60	N.A.
Air Consumption (cfm)	60	N.A.
Air Pressure (psi)	90	N.A.
Electric Power (watts)	N.A.	1400
Weight (kg)	30.0	34.0

TOOL SET

